



码尚科技
MASHANG TEC

CE B

UNIVERSAL

Verify the validity with the QR code



EU TYPE EXAMINATION CERTIFICATE

Certificate No:

Respiratory protective devices, filtering half masks to protect against particles manufactured by

are tested and evaluated according to

EN 149:2001 + A1:2009 Respiratory Protective Devices - Filtering Half Masks to Protect Against Particles - Requirements, Testing, Marking

Based on the type examination conducted with the evaluation of test reports, technical file according to Personal Protective Equipment Regulation (EU) 2016/425 Annex 5, it is approved that the product meets the requirements of the regulation.

Product Definition

Model:

Filtering half mask

Classification:

Here by the manufacturer is allowed to use notified body number (2163) and can fix CE mark, as shown below, on the Category III product models given above, with;

- Issuing an appropriate EU Declaration of Conformity according to **Personal Protective Equipment Regulation (EU) 2016/425 Annex 9**.
- Ongoing successful performance in fulfilment of the requirements set out in **Personal Protective Equipment Regulation (EU) 2016/425** and harmonised standards, ensured by assessments based on **Annex 7 (Module C2)** or **Annex 8 (Module D)** of the regulation no later than 1 year from the beginning of serial production

This certificate is initially issued on 15/07/2020 and will be valid for 5 years, if there is no change in the relevant harmonised standard affecting the essential health and safety requirements.



Suat KACMAZ
UNIVERSAL CERTIFICATION
Director



码尚科技
MASHANG TEC

CE C2

UNIVERSAL

Verify the validity with the QR code



NB 2163

CERTIFICATE OF CONFORMANCE

Certificate No:

Respiratory protective devices, filtering half masks to protect against particles manufactured by

EN 149:2001 + A1:2009 Respiratory Protective Devices - Filtering Half Masks to Protect Against Particles - Requirements, Testing, Marking

Based on the evaluation of test reports and internal quality control audit reports according to EN 149+A1:2009 and Personal Protective Equipment Regulation (EU) 2016/425 Annex VII (Module C2). This certificate implies that the manufactured products show below are in conformance with the approved EU Type Examination model and meets the requirements of the regulation.

Product Definition

Model	Class	EU Type Examination Certificate		
		Serial No	Date	Issuing NB No

Here by the manufacturer is allowed to use notified body number (2163) and can fix CE mark, as shown below, on the Category III product models given above, with;

- Issuing an appropriate EU Declaration of Conformity according to **Personal Protective Equipment Regulation (EU) 2016/425 Annex 9**.
- Taking all measures necessary so that the manufacturing process and its monitoring ensure the homogeneity of production and conformity of the manufactured PPE with the type described in the EU type examination certificate.

This certificate is issued on 15/06/2020 and will be valid for one year, until 15/06/2021 if the manufacturer makes no major change in the product designs and manufacturing processes affecting the product performance on the essential health and safety requirement.



2163

Suat KACMAZ
UNIVERSAL CERTIFICATION
Director



码尚科技
MASHANG TEC

CE检验报告 | CE Test Report



TECHNICAL ASSESSMENT REPORT

REPORT DATE / NO:

Manufacturer:

Address:

This report is for the, given above, manufacturer prepared according to the test results obtained from Trust Right Testing and Certification Service (Zhongshan) Ltd. accredited by IAS (International Accreditation Service), signatory to ILAC MRA, with number TL-861 for the product identified below, dated 15.06.2020 with Serial No based on EN 149: 2001 + A1: 2009 standard and the technical file dated 04 July 2020 Version 01 provided by the manufacturer. The sampling of the product is conducted under our supervision for testing from the manufacturing site of the client.

The technical file of the manufacturer, and risk evaluation against the essential health safety requirements and the test report evaluated for their relation with Essential Requirements of Personal Protective Equipment Regulation and found to be appropriate.

This report is an annex and an integral part of the EU Type Examination Certificate issued to the manufacturer. The test results and issued certificate belongs only to the tested model. The technical report consists of a total of 6 pages.

Product Description: Particle Filtering Half Mask

Classification: FFP2 NR

Model:



UFR-383 12.12.2018 Rev.01





CE检验报告 | CE Test Report



ESSENTIAL HEALTH and SAFETY REQUIREMENTS GIVEN IN EUROPEAN UNION REGULATION EU 2016/425 CORRESPONDING RISKS FOR THE PRODUCT

1.1. Design principles

1.1.1. Ergonomics

PPE must be so designed and manufactured that in the foreseeable conditions of use for which it is intended the user can perform the risk related activity normally whilst enjoying appropriate protection of the highest possible level. The test results with human subjects did not report any problem with the ergonomics of the product.

1.1.2. Levels and classes of protection

1.1.2.1. Highest level of protection possible

The optimum level of protection to be taken into account in the design is that beyond which the constraints by the wearing of the PPE would prevent its effective use during the period of exposure to the risk or normal performance of the activity.

1.1.2.2. Classes of protection appropriate to different levels of risk

Where differing foreseeable conditions of use are such that several levels of the same risk can be distinguished, appropriate classes of protection must be taken into account in the design of the PPE.

1.2. Innocuousness of PPE

1.2.1. Absence of risks and other inherent nuisance factors

PPE must be so designed and manufactured as to preclude risks and other nuisance factors under foreseeable conditions of use. The manufacturer declares in his technical file that according to the results of risk analysis and the material properties they use in the manufacturing, the product has no hazardous content for health.

1.2.1.1. Suitable constituent materials

The materials of which the PPE is made, including any of their possible decomposition products, must not adversely affect the health or safety of users. The material selection is processed in the technical manufacturing process and documented.

1.2.1.2. Satisfactory surface condition of all PPE parts in contact with the user

Any part of the PPE that is in contact or is liable to come into contact with the user when the PPE is worn must be free of rough surfaces, sharp edges, sharp points and the like which could cause excessive irritation or injuries is evaluated and reported in the test report.

1.2.1.3. Maximum permissible user impediment

Any impediment caused by PPE to movements to be made, postures to be adopted and sensory perception must be minimized; nor must PPE cause movements which endanger the user or other persons.

1.3. Comfort and effectiveness

1.3.1. Adaptation of PPE to user morphology

PPE must be designed and manufactured in such a way as to facilitate its correct positioning on the user and to remain in place for the foreseeable period of use, bearing in mind ambient factors, the actions to be carried out and the postures to be adopted. For this purpose, it must be possible to adapt the PPE to fit the morphology of the user by all appropriate means, such as adequate adjustment and attachment systems or the provision of an adequate range of sizes.

1.3.2. Lightness and design strength

PPE must be as light as possible without prejudicing design strength and efficiency.

Apart from the specific additional requirements which they must satisfy in order to provide adequate protection against the risks in question (see 3), PPE must be capable of withstanding the effects of ambient phenomena inherent under the foreseeable conditions of use

1.4. Information supplied by the manufacturer

The notes that must be drawn up by the former and supplied when PPE is placed on the market must contain all relevant information on:

- In addition to the name and address of the manufacturer and/or his authorized representative established in the Community
- Storage, use, cleaning, maintenance, servicing and disinfection, cleaning, maintenance or disinfectant protection recommended by manufacturers must have no adverse effect on PPE or users when applied in accordance with the relevant instructions;
- Performance as recorded during technical tests to check the levels or classes of protection provided by the PPE in question;
- Suitable PPE accessories and the characteristics of appropriate spare parts;
- The classes of protection appropriate to different levels of risk and the corresponding limits of use;
- The obsolescence deadline or period of obsolescence of PPE or certain of its components;
- The type of packaging suitable for transport;
- The significance of any markings (see 2.12)
- Where appropriate the references of the Directives applied in accordance with Article 5(6) (b);
- The name, address and identification number of the notified body involved in the design stage of the PPE

These notes, which must be precise and comprehensible, must be provided at least in the official language(s) of the member state of destination



CE检验报告 | CE Test Report



2. ADDITIONAL REQUIREMENTS COMMON TO SEVERAL CLASSES OR TYPES OF PPE

2.1. PPE incorporating adjustment systems

If PPE incorporates adjustment systems, the latter must be designed and manufactured so that, after adjustment, they do not become undone unintentionally in the foreseeable conditions of use.

2.3. PPE for the face, eyes and respiratory system

Any restriction of the user's face, eyes, field of vision or respiratory system by the PPE shall be minimised.

The screens for those types of PPE must have a degree of optical neutrality that is compatible with the degree of precision and the duration of the activities of the user.

If necessary, such PPE must be treated or provided with means to prevent misting-up.

Models of PPE intended for users requiring sight correction must be compatible with the wearing of spectacles or contact lenses.

2.4. PPE subject to ageing

If it is known that the design performance of new PPE may be significantly affected by ageing, the month and year of manufacture and/or, if possible, the month and year of obsolescence must be indelibly and unambiguously marked on each item of PPE placed on the market and on its packaging.

If the manufacturer is unable to give an undertaking with regard to the useful life of the PPE, his instructions must provide all the information necessary to enable the purchaser or user to establish a reasonable obsolescence month and year, taking into account the quality level of the model and the effective conditions of storage, use, cleaning, servicing and maintenance.

Where appreciable and rapid deterioration in PPE performance is likely to be caused by ageing resulting from the periodic use of a cleaning process recommended by the manufacturer, the latter must, if possible, affix a marking to each item of PPE placed on the market indicating the maximum number of cleaning operations that may be carried out before the equipment needs to be inspected or discarded. Where such a marking is not affixed, the manufacturer must give that information in his instructions. The product is for single use and tested with simulated wearing conditioning.

2.6. PPE for use in potentially explosive atmospheres

PPE intended for use in potentially explosive atmospheres must be designed and manufactured in such a way that it cannot be the source of an electric, electrostatic or impact-induced arc or spark likely to cause an explosive mixture to ignite.

2.8. PPE for intervention in very dangerous situations

The instructions supplied by the manufacturer with PPE for intervention in very dangerous situations must include, in particular, data intended for competent, trained persons who are qualified to interpret them and ensure their application by the user.

The instructions must also describe the procedure to be adopted in order to verify that PPE is correctly adjusted and functional when worn by the user.

Where PPE incorporates an alarm which is activated in the absence of the level of protection normally provided, the alarm must be designed and placed so that it can be perceived by the user in the foreseeable conditions of use.

2.9. PPE incorporating components which can be adjusted or removed by the user

Where PPE incorporates components which can be attached, adjusted or removed by the user for replacement purposes, such components must be designed and manufactured so that they can be easily attached, adjusted and removed without tools.

2.12. PPE bearing one or more identification or recognition marks directly or indirectly relating to health and safety

The identification or recognition marks directly or indirectly relating to health and safety affixed to these types or classes of must preferably take the form of harmonized pictograms or ideograms and must remain perfectly legible throughout the foreseeable useful life of the PPE. In addition, these marks must be complete, precise and comprehensible so as to prevent any misinterpretation; in particular, where such marks incorporate words or sentences, the latter must appear in the official language(s) of the Member State where the equipment is to be used.

If PPE (or a PPE component) is too small to allow all or part of the necessary marking to be affixed, the relevant information must be mentioned on the packing and in the manufacturer's notes.

3. ADDITIONAL REQUIREMENTS SPECIFIC TO PARTICULAR RISKS

3.10.1. Respiratory protection

PPE intended for the protection of the respiratory system must make it possible to supply the user with breathable air when exposed to a polluted atmosphere and/or an atmosphere having an inadequate oxygen concentration.

The breathable air supplied to the user by PPE must be obtained by appropriate means, for example after filtration of the polluted air through PPE or by supply from an external unpolluted source.

The constituent materials and other components of those types of PPE must be chosen or designed and incorporated so as to ensure appropriate user respiration and respiratory hygiene for the period of wear concerned under the foreseeable conditions of use.

The leak-tightness of the facepiece and the pressure drop on inspiration and, in the case of the filtering devices, purification capacity must keep contaminant penetration from a polluted atmosphere low enough not to be prejudicial to the health or hygiene of the user.

The PPE must bear details of the specific characteristics of the equipment which, in conjunction with the instructions, enable a trained and qualified user to employ the PPE correctly.

In the case of filtering equipment, the manufacturer's instructions must also indicate the time limit for the storage of new filters kept in their original packaging.



CE检验报告 | CE Test Report



	Penetration of filter material: Paraffin Oil Testing						
Article 7.9.2	Condition	No. of Sample	Paraffin Oil Testing 95 L/min max (%)	Requirements in accordance with EN 149:2001 + A1:2009	Result		
	(A.R.)	-	2.4	FFP1 ≤ 20 %	Filtering half masks fulfill the requirements of the standard EN EN 149:2001 + A1:2009 given in 7.9.2 in range of the FFP1, FFP2 classes.		
	(A.R.)	-	4.2				
	(A.R.)	-	3.1				
	(S.W.)	-	1.9	FFP2 ≤ 6 %			
	(S.W.)	-	2.3				
	(S.W.)	-	2.1	FFP3 ≤ 1 %			
	(M.S. T.C.)	-	1.8				
	(M.S. T.C.)	-	1.6				
	(M.S. T.C.)	-	1.7				
Conditioning: (M.S.) Mechanical Strength (T.C.) Temperature Conditioning (A.R.) As Received, original (S.W.) Simulated wearing treatment							
Article 7.10	Compatibility with skin: In Practical Performance report, the likelihood of mask materials in contact with the skin causing irritation or other adverse effect on health was not reported. (No negative reporting on practical performance and TIL test results)						
Article 7.11	Flammability:						
	Condition	No. of Sample	Visual inspection	Requirements in accordance with EN 149:2001 + A1:2009	Result		
	(A.R.)	-	Burn for 0s	Filtering half mask shall not burn or not continue to burn for more than 5 s after removal from the flame	Passed Laboratory claims that the tested items did not burn for 5 seconds and fulfils the requirement of the standard		
	(A.R.)	-	Burn for 0s				
	(T.C.)	-	Burn for 0s				
	(T.C.)	-	Burn for 0s				
	Conditioning: (A.R.) As Received, original (T.C.) Temperature Conditioning						
	Article 7.12	Carbon dioxide content of the inhalation air:					
		Condition	No. of Sample	CO ₂ content of the inhalation air [%] by volume	An average CO ₂ content of the inhalation air	Requirements in accordance with EN 149:2001 + A1:2009	Result
		(A.R.)	-	0,31	0,33 [%]	CO ₂ content of the inhalation air shall not exceed an average of 1.0% by volume	Passed Filtering half masks fulfil requirements of the standard
(A.R.)		-	0,33				
(A.R.)		-	0,34				
Conditioning: (A.R.) As Received, original							
Article 7.13		Head harness: In Practical Performance and TIL test reports no adverse effects have been reported for donning and remove of the mask also the results of these tests indicates that the head harness are capable of holding the mask firmly enough.					
Article 7.14		Field of vision: In Practical Performance report, no adverse effects were reported for the field of vision availability when the mask is worn.					
Article 7.15		Exhalation Valve(s): The model under inspection have no valves.					
Article 7.16		Breathing Resistance: Inhalation					
	The overall evaluation of the results gathered for 9 different samples 3 as received, 3 with temperature conditioning, 3 simulated wearing treatment complies with the limits given in the standard for FFP1, FFP2 and FFP3 classes. This is valid for inhalation results for 30 L/min, 95 L/min and exhalation at 160 L/min. The measurement details for each single mask tested are available in the test report.						
	Passed.						



CE检验报告 | CE Test Report



Article 7.17	Clogging: This test is not applied to Particle Filtering Half Mask which is not reusable. <i>(For single shift use devices, the clogging test is optional test. For re-usable devices test is mandatory.)</i>
Article 7.18	Demountable Parts: There are no demountable parts of the mask.
Article 8	Testing: All tests conducted according to Clause 8 of this standard is available in the test report and are evaluated in this report for qualification and classification of the mask.
Article 9	Marking – Packaging: Necessary markings are available on the product package (box). The manufacturer and its trademark is clearly visible. The type of the mask and the classification including the status of re-usability, the reference to EN 149:2001+A1:2009 standard, the end date of shelf life, using and storage instructions and pictograms and CE mark are available on the product package. The above evaluation is based on the technical document for packaging and marking, for box design. Verified on the Annex 9.1 of the technical file. The technical documentation for mask design (drawing) also evaluated for marking requirements, drawing MSNF-01. The mask template (drawing) indicates that the mask will carry information about the manufacturer/ trade mark (-) of manufacturer, Type of mask, the reference to EN 149+A1:2009 standard and classification including the re-usability of the mask. The manufacturer also printed CE mark with our Notified Body number. The mask do not have sub-assemblies. Even the tested sample by the laboratory do not carry necessary marking information as stated in the technical documentation, the manufacturer shall follow marking instructions for serial production. Model drawing MSNF-01 exists in the technical file of the manufacturer, Annex 6 of technical file.
Article 10	Information to be supplied by the manufacturer: In each of the smallest commercially available packaging of the product, implementation (installation instructions) pre-use controls, warning and usage limitations, storage and meanings of symbols / pictograms are defined. User instruction document in the technical file found to be appropriate. The manufacturer shall include this documented user information text in every smallest commercially available package, Annex 8 of technical file.

PREPARED BY

Osman CAMCI
PPE Expert

APPROVED BY

Suat KACMAZ
General Manager



检验报告 | INSPECTION REPORT



中国认可
国际互认
检测
TESTING
CNAS L10118



国检检测
CHINA COMPONENTS TEST

Test Report

(2020) WSZ FHL

Product Name Folding Protective Mask (NON-Medical)

Client _____

Manufacturer _____

Test Type Entrusted inspection

Jiangsu Guojian Testing Technology Co., Ltd.



检验专用章

检验报告 | INSPECTION REPORT


Test Report

[2020] WSZ FHL

Page 1 of 4

Product name	Folding Protective Mask (NON-Medical)	Specification	MSKN95-01
		Brand	Dingying
Client/Add/Tel			
Manufacturer/ Add/Tel			
Sample grade	KN95	Sample number	
Sample quantity	50 pcs	Receiving date of sample	11/06/2020
Test type	Entrusted inspection	Article number/Batch number/Style number	
Test date	21/06/2020~24/06/2020	Testing sites	Testing room
Sample state	Meeting the requirements of testing	Sample description	White
Test standard(s)	GB 2626-2006 Respiratory protective equipment -Non-powered air-purifying particle respirator		
Test items	General requirements, appearance requirements, respiratory resistance, flammability, filter efficiency, head harness, vision, total inward leakage		
Test conclusion	The sample upon testing, the test items meet the requirements of the _____ standard. The detail of test results see on Pages 2-4. <div style="text-align: right;">  Issue date: 30/06/2020 </div>		
Note	For the entrusted sample test, the technical responsibilities are undertaken for the test results of the supplied samples only. <div style="text-align: right;">  报告号 GW6621-2020 </div>		

Approver:



Reviewer:



Chief Tester:



检验报告 | INSPECTION REPORT

Test Report

[2020] WSZ FHL

Page 2 of 4

S.No.	Test item	Unit	Technical requirements	Test result		Single item decision
1	Appearance requirements	—	The surface of the sample shall not be damaged, deformed and have obvious other defects; components and structures shall be able to withstand normal conditions of use and the temperature, humidity and mechanical impact possibly encountered; headband shall be adjustable, and the replaceable mask headband design shall be replaceable; after the pretreatments of temperature, humidity and mechanical strength, the parts shall not fall off, be damaged and deformed.	Meeting the requirements		Qualified
2	Respiratory resistance	Pa	Total inspiratory resistance \leq 350	Untreated	137.4	Qualified
					135.9	
				Pretreated	133.8	
					132.4	
			Total expiratory resistance \leq 250	Untreated	106.7	Qualified
					105.3	
				Pretreated	102.4	
					101.6	
3	Flammability	—	Parts exposed to the flame shall not burn after having been removed from the flame, if burned, the afterflame time shall not exceed 5s.	Untreated	The mask burned. The afterflame time is 0.5s.	Qualified
					The mask burned. The afterflame time is 0.4s.	
				Pretreated	The mask burned. The afterflame time is 0.4s.	
					The mask burned. The afterflame time is 0.4s.	

检验报告 | INSPECTION REPORT

Test Report

[2020] WSZ FHL

Page 3 of 4

S.No.	Test item	Unit	Technical requirements	Test result		Single item decision
4	Head harness	—	Not appearing slippage or breakage to withstand 10N tensile force lasting 10s .	Untreated	No slippage or breakage occurred	Qualified
				Pretreated	No slippage or breakage occurred	Qualified
5	Vision	—	Vision below $\geq 60^\circ$	74.6°		Qualified
6	Filter efficiency	—	$\geq 95.0\%$	Untreated	99.7%	Qualified
					99.8%	
					99.7%	
					99.7%	
					99.6%	
					99.7%	
					99.7%	
					99.6%	
				Pretreated	99.7%	
					99.6%	
					99.7%	
					99.6%	
					99.4%	
					99.5%	

技术负责人
专用章

检验报告 | INSPECTION REPORT

Test Report

[2020] WSZ FHL

Page 4 of 4

Page 4 of 4

S.No.	Test item	Unit	Technical requirements	Test result							Single item decision	
7	Total inward leakage	—	TIL <11% for at least 46 exercises in 50 exercises, and TIL <8% for at least 8 of 10 subjects.	Subjects		E1 (%)	E2 (%)	E3 (%)	E4 (%)	E5 (%)	TIL (%)	Qualified
				Untreated	1 [#]	4.5	5.7	6.3	6.3	4.8	5.5	
					2 [#]	4.3	5.0	5.3	5.8	4.2	4.9	
					3 [#]	4.9	5.6	6.1	6.6	5.1	5.7	
					4 [#]	4.8	5.9	6.4	6.6	5.2	5.8	
					5 [#]	4.8	5.6	5.7	6.4	4.9	5.5	
				Pretreated	6 [#]	4.6	5.4	6.1	5.8	4.5	5.3	
					7 [#]	4.9	5.9	6.5	6.5	5.1	5.8	
					8 [#]	4.6	5.3	5.8	6.1	4.5	5.3	
					9 [#]	5.3	6.6	6.7	7.1	5.7	6.3	
					10 [#]	5.4	6.7	6.8	7.3	5.8	6.4	
Note												

The end



口罩样品 | Mask Samples



口罩包装箱 | Mask Packing Box

【规格|size】59X 20.5 X 58cm



(平面展开图| plane development)

合格证样式 | Certificate Style

CE	2163	(Non-Medical)
CERTIFICATE		
Product Name:	FILTERING HALF MASK	
Model:	MSNF-01	
Size:	15cmx10.5cm	
Material:	Non-woven fabric, Melt-blown fabric Hot-air cotton, PTFE Nanometer fabric	
Standard:	EN 149:2001+A1:2009 to Regulation (EU) 2016/425	
Classification:	FFP2 NR	
Lot Number:	20200605001	
Product Date:	June 10, 2020	
Date of Inspection:	June 10, 2020	
Guarantee period:	2 years from the date of production	
Manufacturer:	Zhejiang Mashang Technology Co., Ltd.	
Address:	No. 366 Shanhai Avenue, Lingxi Town, Cangnan County, Wenzhou City, Zhejiang Province, China 325800	
Inspector:		

